

CUSTOMER BGP IP FILTER POLICY

Dear Customer,

PCCW Global applies inbound filters for our customers' BGP sessions. These inbound filters accept all IPv4 and IPv6 prefixes that customers are allowed to announce to the internet, either directly or on behalf of their own customers.

To ensure your BGP announcements are accepted by our network, please follow these steps:

1. Register your as-set and route objects in one of the IRR databases listed in this document.

In doing so, please ensure you meet the following requirements:

- Include all of your ASNs and downstream customers' ASNs in your as-set.
- · Do not include your other transits and peers in your as-set.
- Create route objects for all of your IPv4 and IPv6 address space resources.
- · If any downstream customers are in your as-set, make sure route objects for those resources exist as well
- 2. In order to further improve security, please also consider creating RPKI ROAs with the same records. • If you've created RPKI ROAs, please make sure the ASNs in the ROAs match with the origins in the route objects.

IRR DATABASES

PCCW Global makes use of as-set and route objects to filter BGP announcements sent by our customers.

Here is a list of the mirrored IRR databases along with their supported objects:

DATA- BASE	AS- SET	ROUTE	ROUTE OBJECT PREFERENCE	MIRRORED EVERY
RIPE	✓	Authorised only	900	60 mins
ARIN	✓	Authorised only	900	60 mins
APNIC	✓	✓	900	60 mins
JPIRR	✓	✓	900	24 hours
AFRINIC	✓	✓	900	60 mins
LACNIC	✓	✓	900	60 mins
IDNIC	✓	✓	900	60 mins
ALTDB	✓	✓	200	24 hours
RADB	✓	✓	100	60 mins

ROUTE OBJECT PREFERENCE

IRR Databases are sorted by preference. In the case of overlapping route objects, those with higher preference are mirrored and the others discarded. For example, if two **route** objects for the same prefix exist in AFRINIC (preference 900) and RADB (preference 100), those from AFRINIC's database are mirrored and the others are discarded.

In the case of databases with the same preference, none of the overlapping route objects are discarded.

RPKI ROAS

PCCW Global discards inbound BGP announcements. from customers and peers that are considered INVALID by the RPKI framework. This filtering takes place BEFORE those built on top of the IRR databases. This means that INVALID ROAs get discarded regardless of any route objects created by the user. No action is enforced by the RPKI filter for VALID or UNKNOWN announcements. which are accepted or rejected depending on IRR database lookup.

PCCW Global mirrors RPKI ROA repository systems every 60 minutes.









CONSOLE CONNECT | CUSTOMER BGP IP FILTER POLICY